Approved For Release 2003/02/27: CIA-RDP78B04747A003100030059-1 Inspection Branch/PD/OL DATE 26 February 1962 REPORT PERIOD: CONTRACT # REPORT # STATINTL (If final, so state) Contractor Address Commodity/Service Breachourd Classification Unclassified No. Of Prototypes (1) Contract Completion Date 5 JAN 62 The Contract is on schedule: Yes The Contractor will remain within his allocated funds: Yes No An extension of time will be necessary: Yes X No All phases of the technical progress are satisfactory: Yes______Yes______ The overall performance of this Contractor is: Satisfactory NOTE: If unsatisfactory or subject to improvement indicate reasons under Subject to improvement comments. Unsatisfactory STATINTL Comments: Equipment Generation was witnessed by **STATINTL** on 9 February 1962, at the facility. This demonstration showed the feasibility of edge and line detection as an aid to high precision mensuration. A final report and various photographs of the "breadboard" have been received. That the breadboard demonstrating the feasibility of Recommended Action: edge and lime detection techniques be accepted as the natisfactory completion of this contract. It is further recommended that ____ be contacted to return the few items incorporated in the breadboard which were purchased pursuant to this contract. It is understood that the vast majority STATINTL of equipment used in the breadboard was equipment from the Image Correlator Date of last visit to Contractor's Plant: 9 February 1962 STATINTL

Declass Review by NIMA/DOD

STATINTL

Inspected by

Division & Extension

STAT

STAT

27 February 1962

MEMORANDUM FOR: Chief, Technical Intelligence Division	<i>y</i>
THROUGH: Chief, Technical Plans & Development Staff	
SUBJECT: Final Acceptance of Contract: Task Order #3, STATINTL	STAT
1. The purpose of the edge and line detection program is to invest the feasibility of using the flying spot scanner technique to make accurate repeatable photogrammetric measurements. The program is to develop laborate equipment which aligns an edge in a photograph with the direction of a fly spot scanner and to display the actual profile of the edge. The mode of tion is to output a scan, moving parallel to the edge, which will be corresponded with the scan of the photograph ramp, one increasing in density while the other decreases. The results of the two correlations (multiplicand integration) of the products of a single scan will be developed to yie a null when the scan is parallel to the edge. A display is provided of the average edge profile of the scanned region. Measurements between edges can be made by use of the profile display and a Vernier adjustment.	te atory ying opera- elated y cation eld
STATINTL STATINTL and on 9 February 1962 at the facility who demonstration in the state of the	
conducted by	STATINTL
After discussions with personnel it appears to the undersigned that the feasibility study witnessed by conclusion to this development contract, but that the development to date cannot be directly incorporated in any high precision measuring equipment such as a Comparator or Dual Screen Comparator. It is believed to before such equipment is modified to incorporate edge and line detecting techniques that a prototype be developed and tested in equipment not involved in production work. The problem of providing the comparator operator with a CRT presentation of the integrated edge is feasible technically, but it still the problem of the comparator operator to make the decision as to when the alarm of the comparator operator to make the decision as to when the alarm of the comparator operator to make the decision as to when the alarm of the comparator operator to make the decision as to when the comparator operator to make the decision as to when the alarm of the comparator operator to make the decision as to when the comparator operator to make the decision as to when the comparator operator to make the decision as to when the comparator operator to make the decision as to when the comparator operator to make the decision as to when the comparator operator to make the decision as to when the comparator operator to make the decision as to when the comparator operator to make the decision as to when the comparator operator to make the decision as to when the comparator operator to make the decision as to when the comparator operator to make the decision as to when the comparator operator to make the decision as to when the comparator operator to make the decision as to when the comparator operator to make the decision as to when the comparator operator to make the decision as to when the comparator operator to make the decision as to when the comparator operator to make the decision as to when the comparator operator to make the decision as to when the comparator operator to the comparator operator operator to the co	STATINTL Chat ved is STATINITI
on the slope of the edge the edge actually is. This would require training and experience in some depth. It is, therefore, recommended that TID/TAB, determine whether he believes the techniques seen to date warrant further development. It is also recommended that the GIANT which is presently being modified for use as a rear projection comparator considered as the test bed for any future work in edge and line detection.	g STAT
STATINTL 3. A final report has been received from and various photos wer taken of the breadboard during final acceptance. The development pursuant to Contract Task Order #3, is accepted, as noted in the inspect report form provided by PD/OL.	e STATINTL
Approved For Release 2003/02/27 : GIA-RDP78B04747A003100030059-1	
AC/TDB	